

AERODYNAMICS

for FITRS

FRONT SPORTS GRILLE -



Replaces the OE front grille. Comes with MUGEN metal emblem. Vacuum moulded, PPE construction. Colour: Gloss Black (Matt Black around emblem)

75100-XLFD-K0S0



SA STYLING SET

Version Coloured × Black Side Spoiler

Front under spoiler, Side spoiler "Coloured × Black" ×2 and Rear under spoiler per set.

FIT RS Coloured 2.7h 61000-XLFD-K1S0-**



Two-toned finish coloured + Black

SA SIDE SPOILER "COLOURED × BLACK" —

Two-piece structure achieves visual sharpness in design. Fixes to OEM lower side panels. Right and left hand per set. Vacuum moulded, PPE construction. FIT RS 1.0h 70219-XLFD-K1S0-**

Colours available: Body Colour/Gloss Black Crystal black pearl is not available.



SE STYLING SET

Version Coloured Side Spoiler

Front under spoiler, Side spoiler (×2) and Rear under spoiler per set.

FIT RS Coloured 2.7h 61000-XLFD-K3S0-**



SIDE SPOILER "COLOURED"

Two-piece structure achieves visual sharpness in design, Fixes to OEM lower side panels. Right and left hand per set. Vacuum moulded, PPE construction. FIT RS Coloured 1.0h 70219-XLFD-K0S0-**

Colours available: Premium White Pearl Silver Storm Yellow Pearl Premium Crystal Black Pearl Deep Sapphire Blue Pearl Sunset Orange

FRONT UNDER SPOILER



FIT RS

Coloured ¥ 65,100 0.7h (税抜価格¥62,000) 71110-XLFD-K1S0-**

COLOUR VERSION Premium yellow pearl Crystal black pearl Deep sapphire pearl Sunset orange (NH624P) (NH731P) (YR585)

VENTILATED VISOR





Rubber plate prevents the emitted air re-entering the car.

Typically with ordinary visors, with the side window open even slightly the air emitted from the front opening flows upward along the window and re-enters the passenger compartment, However, the MUGEN visor design has a unique configuration that prevents the back flow and efficiently uses negative pressure to discharge the air from the passenger compartment. Furthermore, wind noise is significantly reduced compared to that generated by many other visor fitments, while at the same time rainwater is prevented from entering the passenger compartment; both factors that provide a substantial improvement in passenger comfort. Smoked acrylic, 2pcs each of the front and rear visors / a set, PAT

0.4h 72400-XLF-K0S0



WING SPOILER

FIT RS

Coloured 84112-XLFD-K0S0-**

Tailgate mounted rear wing spoiler and tailgate cover, replaces OE tailgate spoiler and comes with MUGEN metal emblem,

Wing: Blow moulded ABS construction Tailgate Cover: Blow moulded ABS construction Colour: Matt Black





Vehicle with the OE fog light Vehicle with the aero illumination

Three-piece large front under spoiler exclusive to the RS model. Installs on OE bumper, with LED fog lights, which are available separately as an option. Can be combined with the aero illumination. Vacuum moulded, PPE construction.



LED FOG LIGHT (OPTION)

08V31-XG8-LW01

The combination of the high performance projector unit plus bright LED gives an ideal light distribution pattern. Super luminosity LED offers excellent visibility with low power consumption, and long life. Available as an optional part for front under spoiler. Beam colour white.

For installation; should be installed with front under skirt removed. Not suitable for use with OEM skirt.

LED FOG LIGHT ATTACHMENT

Set consists of: wiring harness, attachment and light switch.

For RS 0.6h 08V31-XLFD-K2S0

AERO ILLUMINATION (OPTION)



1.0h 33400-XLFD-K0S0

Aero illumination with super luminosity bright White LED lighting. Aero illumination is activated whenever the ignition switch is in an on position. Replaces the OE front grille. Comes with MUGEN metal emblem, Vacuum moulded, PPE construction.

For installation; should be installed with front bumper removed. Not suitable for use with OEM bumper.

REAR UNDER SPOILER



FIT RS

Coloured

84111-XLFD-K1S0-**

Large rear under spoiler exclusive to RS model. Attaches to bottom of OE rear bumper, with separate Gloss Black diffuser is a separate piece. Vacuum moulded, PPE construction.

AERODYNAMICS for FIT HYBRID

WING SPOILER



FIT HYBRID

Tailgate mounted rear wing spoiler, comes with MUGEN metal emblem, Blow moulded ABS construction.

Coloured 84112-XLF-K1S0-** Unpainted 84112-XLF-K1S0-ZZ

SA SEE REAR UNDER SPOILER



Designed to be attached to the bottom part of OEM bumper. Vacuum moulded. PPE construction.

Coloured 0.6h 84111-XLFD-K0S0-**
Unpainted 0.6h 84111-XLFD-K0S0-ZZ

SA STYLING SET

Version Coloured × Silver Side Spoiler Front under spoiler, Side spoiler ("Two-Tone" ×2)

and Rear under spoiler per set. Not available for Alabaster silver M.

FIT HYBRID Coloured 2.2h 61000-XLFD-K2S0-**

Two-toned finish: Coloured + Silver

SA SIDE SPOILER "Two-Tone" -

Two-piece structure achieves visual sharpness in design, Fixes to OEM lower side panels. Right and left hand per set. Vacuum moulded, PPE construction. FIT HYBRID 1.0h 70219-XLFD-K2S0-**

Colours available: Body Colour/Silver Alabaster silver metallic is not available.

SIDE SPOILER "COLOURED"

Two-piece structure achieves visual sharpness in design, Fixes to OEM lower side panels. Right and left hand per set. Vacuum moulded, PPE construction. 1.0h 70219-XLFD-K0S0-** FIT HYBRID Coloured

Unpainted 1.0h 70219-XLFD-K0S0-ZZ

Colours available: Premium White Pearl Silver Storm Yellow Pearl Premium Crystal Black Pearl Deep Sapphire Blue Pearl Sunset Orange





assembled

Wheels: XJ/Spark Silver

Photo: FIT HYBRID Premium white pearl

Installs on to OE bumper. LED fog light available as option. Vacuum moulded, PPE construction.

FIT HYBRID Coloured

0.6h 71110-XLFD-K0S0-** Unpainted 0.6h 71110-XLFD-K0S0-ZZ

STYLING SET

Version Coloured Side Spoiler


Front under spoiler, Side spoiler (×2) and Rear under spoiler per set.

Unpainted 2.2h 61000-XLFD-K0S0-ZZ

2.2h 61000-XLFD-K0S0-**



VENTILATED VISOR



0.4h 72400-XLF-K0S0

Typically with ordinary visors, with the side window open even slightly the air emitted from the front opening flows upward along the window and re-enters the passenger compartment. However, the MUGEN visor design has a unique configuration that prevents the back flow and efficiently uses negative pressure to discharge the air from the passenger compartment. Furthermore, wind noise is significantly reduced compared to that generated by many other visor fitments, while at the same time rainwater is prevented from entering

the passenger compartment; both factors that provide a substantial improvement in passenger comfort. Smoked acrylic, 2pcs each of the front and rear visors / a set. PAT

Premium white pearl (NH624P)

Alabaster silver metallic (NH700M)

Premium yellow pearl (Y66P)

Milano red (B81)

Crystal black pearl (NH731P) CB

Azure blue metallic (B568M) AB

Fresh lime metallic (GY27M)

Unpainted

LED FOG LIGHT (OPTION)





08V31-XG8-LW01

The combination of the high performance projector unit plus LED gives an ideal light distribution pattern. Super luminosity LED offers excellent visibility with low power consumption, and long life. Available as an optional part for front under spoiler. Beam colour white.

For installation; should be installed with front under skirt removed. Not suitable for use with OEM skirt.

LED FOG LIGHT ATTACHMENT



Set consists of: wiring harness, attachment, light switch.

1.6h 08V31-XLFD-K1S0

HYBRID ILLUMINATION GRILLI







FIT HYBRID

1.0h

Illumination is off 75100-XLFD-K1S0

Whenever the ignition is switched on "HYBRID" is illuminated in the centre of the grille highlighting the hybrid presence. Replaces the OE front grille. Comes with MUGEN metal emblem, Vacuum moulded, PPE construction.

Colour: Upper area / Silver, Lower area / Matt black "HYBRID" illumination cannot be activated independently.

FRONT SPORTS GRILLE



0.8h 75100-XLFD-K0S0

Replaces the OE front grille. Comes with MUGEN metal emblem,

Vacuum moulded, PPE construction.

Colour: Gloss Black (Matt Black around emblem)

AERODYNAMICS

for FIT

FRONT SPORTS GRILLE -



Replaces the OE front grille. Comes with MUGEN metal emblem, Vacuum moulded, PPE construction. Colour: Gloss Black (Matt Black around emblem)

0.8h 75100-XLFD-K0S0



STYLING SET

Front under spoiler, Side spoiler (×2) and Rear under spoiler per set.

FIT

2.2h 61000-XLFD-K0S0-**

Unpainted 2.2h 61000-XLFD-K0S0-ZZ



With no LED foa liaht

Installs on to OE bumper. LED fog light available as option. Vacuum moulded, PPE construction.

Coloured 0.6h 71110-XLFD-K0S0-**

Unpainted 0.6h 71110-XLFD-K0S0-ZZ

LED **FOG LIGHT** (OPTION)






08V31-XG8-LW01


The combination of the high performance projector unit plus bright LED gives an ideal light distribution pattern. Super luminosity LED offers excellent visibility with low power consumption, and long life. Available as an optional part for front under spoiler. Beam colour white.

For installation the attachment sold separately is required. Vehicle with ECON or without it are selectable. For installation; should be installed with front under skirt removed. Not suitable for use with OEM skirt.



VENTILATED VISOR





Rubber plate prevents the emitted air coming back into the car.

0.4h 72400-XLF-K0S0

Typically with ordinary visors, with the side window open even slightly the air emitted from the front opening flows upward along the window and re-enters the passenger compartment. However, the MUGEN visor design has a unique configuration that prevents the back flow and efficiently uses negative pressure to discharge the air from the passenger compartment. Furthermore, wind noise is significantly reduced compared to that generated by many other visor fitments, while at the same time rainwater is prevented from entering the passenger compartment; both factors that provide a substantial improvement in passenger comfort. Smoked acrylic, 2pcs each of the front and rear visors / a set, PAT

Photo: FIT Colour: Milano red Wheels: NR/Mirror Face

COLOUR VERSION

Premium white pearl

Alabaster silver metallic

Premium yellow pearl

Milano red (R81)

Crystal black pearl

Azure blue metallic

Unpainted

LED FOG LIGHT ATTACHMENT

1.5h

For ECON unequiped

08V31-XLFD-K0S0

Switch for ECON unequiped

Set consists of: wiring harness, attachment and light switch

For ECON equiped

08V31-XLFD-K1S0



Switch for ECON equiped

SIDE SPOILER



Two-piece structure achieves visual sharpness in design. Fixes to OEM lower side panels. Right and left hand per set. Vacuum moulded, PPE construction.

1.0h 70219-XLFD-K0S0-** Coloured Unpainted 1.0h 70219-XLFD-K0S0-ZZ

Colours available: Premium White Pearl Silver Storm Yellow Pearl Premium Crystal Black Pearl Deep Sapphire Blue Pearl Sunset Orange



Designed to be attached to the bottom part of OEM bumper Vacuum moulded, PPE construction.

Coloured 0.6h 84111-XLFD-K0S0-**

Unpainted 0.6h 84111-XLFD-K0S0-ZZ

WING SPOILER



Tailgate mounted rear wing spoiler, comes with MUGEN metal emblem, Blow moulded ABS construction

Coloured 0.7h 84112-XLF-K1S0-**

Unpainted 0.7h 84112-XLF-K1S0-ZZ



Sports Silencer

for FITRS Straight design silencer which is tuned exclusively for RS model, giving instantaneous response and a pleasant, sporty exhaust note. The stainless steel finisher has a 90mm diameter, and the system is certified by JASMA. Suitable for fitment with either MUGEN or OE rear under spoiler. Stainless steel construction





FIT RS

0.5h 18000-XLFD-K1S0

for FIT HYBRID With a Delta finisher that actually improves air flow this silencer is tuned exclusively for HYBRID models.

Suitable for fitment with either MUGEN or OE rear under spoiler. Stainless steel construction and JASMA certified.





FIT HYBRID

18000-XLFD-K2S0

Silencer designed specific to offer excellent exhaust efficiency and sound deadening characteristics on FIT.

Finisher size is \$\phi 90\$. Suitable for fitment with either MUGEN or OE rear under spoiler. Stainless steel construction and JASMA certified.





0.5h 18000-XLFD-K0S0

Hi-Pressure Radiator Cap

Opening valve pressure in increased to work effectively in high-load operation such as circuit driving. Opening pressure 1.3kgf/cm²[127kpa] 0.1h 19045-XGER-0000





PERFORMANCE


Hi-Performance Air Filter





0.1h 17220-XLF-0000

Direct replacement for the OE air cleaner, High efficent air filter whose inhalation resistance is lowered by 12%. With a filter maintenance kit sold separately, the air filter can be used repeatedly.



Inhalation resistance to Air flow

FIT RS

The graph on left shows comparision between OE air box + OE filter and OF air box + Hi-performance air filter

Filter Maintenance Kit

Exclusive filter washer (spray) and filter oil (aerosol) as a set. 90000-YZ0-5000-99

Copper Fiber Clutch System



FIT RS 6MT

4.0h 22000-XLFD-K0S0

The copper fibre clutch system is developed for ease of use on the street, combined with a more positive direct feeling and response and crisp gearshifts while sports driving.

A newly-developed non-asbestos material containing copper and resin has been used for the friction plate allowing good frictional properties for the transfer of power in both low and high temperature conditions. Operating load: 5600Nm

Kit comprises of pressure plate assembly, friction disc and release bearing.

Metal Clutch Set



FIT RS 6MT 22000-XLFD-S0N0

Performance, drivability, and, durability during sports driving on circuit course were considered to develop this metal clutch system. Low-density metal was used as material for discs, which can keep high transfer performance. The clutch weight is reduced by 7% compared to the OEM clutch. To increase heat capacity, disc pads were enlarged to get higher heat resistance. All the above improvements considered, this would be the most ideal metal clutch system for the driving enthusiasts.

Load: 5.600N · m Cover, disc, release bearing / a set.

Hi-Performance Oil Element

The filtering area and position of the filtering material are optimized in order to eliminate sludge deposits as much as possible, and also contributes to the 10% reduction of the pressure loss experienced when compared with the OEM oil element. Owing to the "Y" shape cross section of the newly developed filtering fibres, sludge deposits are prevented from reentering into the system, reducing friction on the inner surfaces. Acrylic rubber (gasket) and silicon rubber (anti-drain), assist the oil filter element in resisting the high temperature conditions of the VTEC engine.



15400-XK5B-0000 Enlarged picture of the filter element

Relation between grain diameter and filtering efficiency (Compared with other makers) Filtering efficiency differen 60 40

粉径 (μm) Chart shows relation between grain diameter and filtering efficiency Chart above shows the relation between grain diameter and filtering efficiency Filtering efficiency improves by 36% compared with that of OEM filter.

Engine Treatment Oil MT105

Major ingredient, MODTC (Organic molybdenum) is quickly penetrated into the metal friction surface and makes a smooth metal surface by forming strong lubricating surface which in turn reduces the friction resistance and engine noise, and minimizes the loss of engine power as a result.

Amount: 200ml 90000-YZ0-105



Oil Filler Cap

Precision-machined from solid aluminium and hard-anodised finished these oil filler caps remain securely in place while enhancing the look of the engine bay. Available in 5 colours: Gold, Silver, Red, Blue, and Black



[CHAMPAGNE GOLD]15610-XG8-K1S0-CG [SILVER] 15610-XG8-K1S0-S [RED] 15610-XG8-K1S0-R [BLUE] 15610-XG8-K1S0-BU [BLACK] 15610-XG8-K1S0-BL

HANDLING

SPORTS SUSPENSION



for FITRS Sports suspension tuned exclusively for RS to enhance cornering performance and high-speed stability during sports driving. The large diameter (Ø32) damper piston provides precise and stable damping from low speed to high speed piston rates. Uprated rebound spring provides excellent vehicle support to achieve more stable cornering. Suspension is developed individually to take into account the weight differential between the 6MT and CVT transmissions. All 4 dampers and springs are included in the set. Vehicle's height is reduced by 20 to 25mm.

	•	•	
	Damping force(0.3/s) Expansion/ Comprssion	Spring rate-N/mm (OEM)	Vehicle height comprison with OEM(mm)
FRONT	149 / 116	6MT 22.5 (20.6) CVT 23.0 (20.6)	-20~-25
REAR	167 / 88	6MT 22.0 (19.1) CVT 22.0 (19.1)	-20:23

* kgf/mm 6MT FRONT: 2.3 (2.1) REAR: 2.2 (1.9) CVT FRONT: 2.3 (2.1) REAR: 2.2 (1.9)

ŀΚ١

FIT RS CVT 3.0h 50000-XLFD-K1S0

for FITHYBRID Suspension tuned specifically to take into consideration the weight and position of the IMA battery installation, and to maintain the ideal front and rear weight distribution of the car for sporty handling and drivability. All 4 dampers and springs are included in the set. Vehicle's height is reduced by 20 to 25mm.

	Damping force(0.3/s) Expansion/ Compression	Spring rate-N/mm (OEM)	Vehicle height comprison with OEM(mm)
FRONT	149 / 113	20.5 (21.0)	-20~-25
REAR	144 / 112	21.0 (19.1)	

kaf/mm FRONT: 2.1 (2.1) REAR: 2.1 (1.9)

FIT HYBRID 3.0h 50000-XLFD-K2S0

With optimized damping force and spring rates cornering performance and high-speed stability are greatly improved without sacrificing drivability on ordinary streets. All 4 dampers and springs are included in the set. Vehicle's height is reduced by 20 to 25mm.

	Damping force(0.3/s) Expansion/ Comprssion	Spring rate-N/mm (OEM)	Vehicle height comprison with OEM(mm)
FRONT	141 / 185*1	20.0 (19.6)	-20~-25
REAR	143 / 115**1	18.0 (19.1)	-20~-25

FIT CVT FF 3.0h 50000-XLF-K1S0

ALUMINIUM WHEEL XJ

Twin Air Valve

Disk design

By use of separate in and out valves filling efficiency can be improved when nitrogen gas is injected.

Mesh shape releases heat efficiently.

Hub fitting design exclusive

Black metal coat and spark silver are available.

for Honda vehicles

Enhancing rigidity between

wheel and hub to improve driving performance.

16×61/2 Jinset 55 4H P.C.D.100

Colour

Lightweight"XJ"wheel with high rigidity spoke pattern designed to allow efficient dispersal of heat. The distinctive convex and concave shape design gives a strong and sharp impression. Hub fitting exclusive to Honda cars is adopted to improve installation stiffness between wheel and hub to achieve improvement of driving performance. In addition, twin air valves are installed diagonally opposite to each other which allow the use of separate valves for in/out in order to improve the filling efficiency when using Nitrogen for tyre inflation.Colours available:Black metal coat Spark silver Size:18 x 8 1/2J inset 55, Alloy one piece construction. Special wheel nuts are sold separately. Please note; OEM wheel nuts must not be used with these wheels, special wheel nuts are sold separately. . Recommended tire size:

Black Metal Coat





Black Metal Coat 16×6 1/2J Inset 55 42700-XJ4-665C-55



Spark Silver 16×6 1/2J Inset 55 0.7h

42700-XJ4-665P-55

ALUMINIUM WHEEL NR

One piece cast wheel featuring 8 spokes giving excellent rigidity. The NR wheel also utilizes the hub fit design, which is exclusive to Honda vehicles. Colours available: Racing White Mirror face Silver Please note; OEM wheel nuts must not be used with these wheels, special wheel nuts are sold separately. Recommended tire size:



Racing White 15×6 1/2JJ Inset 50 42700-NR4B-565W-50



Mirror Face 15×6 1/2JJ Inset 50 42700-NR4B-565M-50



15×6 1/2JJ Inset 50 42700-NR4B-565S-50



WHEEL NUT & LOCK NUT SET





12 wheel nuts (taper type) and 4 lock nuts per set. Colours available:Silver,Black

Silver 08181-M07-K0S0-S Black 08181-M07-K0S0-BL



BRAKING

Hi-Performance Brake System


To secure the same or better quality as the OEM brake system, extensive testing was carried out both on the dyno and at circuits.

Brake Rotor

Five slits engraved on each surface of the brake rotor remove carbonized surface caused by exposure to heat and can keep the surface always clean, which in the end helps stable braking. Furthermore, the material used for Super GT, high carbon stronger agaist heat crack and having higher µ characteristics, is adopted for 45250-XLF-K1S0, which can maximize performance of the pads. A set of both front and rear.

[FRONT] 0.8h 45250-XLF-K0S0*1 0.8h 45250-XLF-K1S0*2

[REAR] 0.8h 43250-XLF-K0S0*3



The width, depth and angle of these grooves were determined through tests to find the correct balance between coefficient of friction and brake performance. These grooves are also milled asymmetrically front to rear to minimize any unpleasant brake judder.

Brake Pad

-Type Touring-

Braking performance during street driving was prioritized for its development. Initial point of braking and pedal touch are improved. Front and rear pad / a set

[FRONT]





0.7h 45022-XK7-K000

0.7h 45022-XLF-K200

0.7h 45022-XLQ-K000

[REAR]





0.7h 43022-XK7D-K000

-Type Sport-

Covering daily to sports driving, our brake pads respond precisely to driver braking input, which leads to fine driveability. Right and left fronts and rears per each set.





FIT RS 0.7h 45022-XLT-K000





FIT RS 0.7h 43022-XLF-K000

MICROMESH BRAKE LINE

The brake line reinforced with stainless steel wire mesh increases the feeling of rigidity as the driver steps on the brake pedal and is an invaluable tuning part to delicately modulate the pedal stopping force. Since the diameter of the outer braid of a standard stainless steel mesh brake line is made of single stainless steel wire of 0.3mm, it lacks flexibility and fatigue durability. In contrast, the outer braid adopted by MUGEN's micromesh brake line is made of seven very fine wires, which are woven together to produce a single steel wire with a diameter of 0.21mm, which in turn is woven with other similar single wires to produce a wire mesh, significantly improving the flexibility and

The MUGEN brake line is reinforced with stainless steel wire mesh and was the first such wire mesh to meet the Federal Motor Vehicle Safety Standard No. 106 of the U.S. (FMVSS)

For Rear Drum Brake 4 lines per set 1.1h 46400-XLF -K0S0 For Rear Disk Brake 6 lines per set 1.3h 46400-XLF -K1S0

Hi-Performance Brake Fluid



Specially developed high performance brake fluid for Honda vehicles, It helps prevent vapour lock with a dry boiling point of 327°C and a wet boiling point of 202°C, significantly exceeding the BF5 Standard. The high boiling points are maintained for a longer period due to the resistance to humidity absorption, which can cause lowering of the boiling point, and therefore the product has an increased useful life. The product contributes to the overall excellent performance of the MUGEN braking system during high speed driving.

90000-XYB -B000

Reserve Tank Cover




In a stylish MUGEN-branded design the reservoir tank cover for the brake and clutch fluid absorbs leakage which can occur due to various factors during driving. Fireproof material ensures increased safety.

0.1h 90000-YZ7-0054

EQUIPMENT

Carbon Door Mirror Cover





Not Available for Fender Winker model

Enlarged picture of the surface

0.5h 76205-XMB-K0S0

Door mirror cover made of dry carbon exclusively designed for FIT. Covered with UV clear coating which prevents the mirror from deterioration including color fade away.

Hydrophilic Mirror





0.3h 76200-XLFD-K0S0

Enlarged image of MUGEN Logo

Multi-layer coated, blue colour mirror which diminishes ultraviolet light and sun light.

When driving, this mirror eliminates dangerous rear view mirror glare and reduces eye fatigue, making it safer for drivers. Hydrophilic coated mirrors developed by photocatalyst technology can clear driver's vision while driving in rain. The modified curvature of the mirror (RH side - 1000R, LH side - 1000R), allows awider range of view for the driver. Supplied as a direct replacement for the OEM mirror glasses, and complete with laser-printed MUGEN logo. Please note; the heat demisting function of the mirrors will be lost due to installation of these mirrors.

Number Plate Bolts





High grade machined number plate bolt, comprising of stainless steel head (washer collar) and bolt. Laser printed with MUGEN POWER. Hexagonal socket-head is adopted as a protection against theft. Head size: φ20 t=3mm. 2 bolts per a set

0.1h 75700-XG8-K0S0

INTERIOR

Assist Meters







Water temperature and oil temperature meters are all contained in the meter cowl exclusively designed for FIT.

The shape and position of the cowling is designed and arranged so as not to obscure the driver's line of sight, but at the same time to be easily viewed whilst driving Meter diameter is \$\phi\$60mm

Includes sensors, special harness, and the control unit. GFRP housing; colour of unit to match OEM meter panel



Not available for fender winker model. [2,3h]

78200-XLF-K0S0





the figures and scales in the panel board are

illuminated in Green and the needles are illuminated



When the side lights and head lights are turned on, The peak value of each meter during vehicle running is indicated by the respective needle.



[Warning mode]

MUGEN FIT TECHNICAL FEATURES

Whenever a reading from the engine sensors exceeds the user pre-set value, the warning LED in the panel board lights up (in case of oil pressure gauge, if the value is less than the set value, then the warning

A useful replay mode in which each meter simultaneously records and reproduces the running condition for a maximum of 40 seconds is

MUGEN Metal Logo Emblem

High grade three dimensional Chrome-plated metal emblem Available in white or Black. Size: 20 (long) x 165 (width) mm



Chrome plated / White

Recommended colour combination: Premium White P

0.4h 90000-YZ8-DV62-WH





0.4h 90000-YZ8-DV62-BK



INTERIOR **Sports Mat**

The front of the mat is Black with a Red edge, giving a sports-oriented impression. Under the embroidered MUGEN logo, three coloured bands depicting the corporate colours of MUGEN are also embroidered. Highly durable hard-wearing nylon is used on the front part of the mat, while on the rear, polyester material and special spikes help to keep the mat in position during use. The mats also feature durable and non-slip heel pads. Tabs on both side of the mat prevent the mat from moving. Designed safety.



MUGEN logo is embroidered separately, which helps improve the texture.



Edges are over-locked with Red thread, which highlights the sports-oriented features in the Black base mat.



Highly durable heel pads are adopted for both driver and passenger mats and shaped into a special design to prevent slippage.






Mat for the driver is equipped with two locks to prevent sliding. Simple lock action for removing mat improves convenience when cleaning.



Edges are over-locked with Red thread, which highlights the sports-oriented features in the Black base mat.



Black x RED 0.2h 08P15-XLFD-K0S0-RD



The under side is covered with polyester material preventing the matt from sliding away and which can contribute to sporty driving.



MUGEN collar tags are stitched on the rear floor mat.



The under side is covered with polyester material preventing the matt from sliding away and which can contribute to sporty driving.

Carbon Interior Rear-view Mirror Cover



Enlarged picture of the interior 76450-XLY-K0S0 mirror cover surface

Dynamically designed dry carbon room mirror cover with printed MUGEN logo.

0.1h

Interior Rear-view Mirror Cover



Chrome plated



Dynamicaly designed room Mirror cover with printed MUGEN Logo. Colour (MUGEN code) : Premium White Pearl (PW) Alabaster Silver Metallic (AS) Milano Red (MR)



Coloured

76450-XKK-K0S0-**(Colour code)

www.mugen-power.com/automobile/products/fit/



M-TEC Co., Ltd. 2-15-11 Hizaoricho Asakashi Saitamaken 351-8586 JAPAN 048-462-313

http://www.mugen-power.com